

3 Knuckle Half Mortise Hinges

Heavy Weight Concealed Bearing

CB1921R – (ANSI A8211) Steel – polished and plated or phosphated and prime coated for painting


CB1981R – (ANSI A2211) Brass or bronze – polished and plated or painted

CB1981R (32) – (ANSI A5211) Stainless steel – highly polished

CB1981R (32D) – (ANSI A5211) Stainless steel – satin finish



- For heavy, or high frequency hollow metal, or wood doors, hung on channel iron frames
- Concealed bearing for trouble-free, long life – no oil, no grease, no maintenance
- Pins in nonferrous hinges are stainless steel
- Reversible flush tips and pins
- Hinges can be furnished with hospital tips (HT)
- Limited lifetime warranty
- Available with exposed tips (ET)



Measurements below

Size Length of Joint	Width		Offset (C)	Gauge of Metal	Flat Head Screws Per Piece		Quantity Per Box	Quantity Per Case	Case Weight	
	Frame Leaf (A)	Door Leaf (B)			Frame Leaf	Door Leaf			Bronze	Steel
Inches (mm)	Inches (mm)	Inches (mm)	Inches (mm)	Inches (mm)					Lbs. (Kg)	Lbs. (Kg)
4 1/2 (114)	1 1/2 (38.1)	2 1/8 (54)	1/2 (12.7)	.180 (4.6)	3-12-24 x 1/2	4-12-24 X1/2	3 ea.	30 ea.	36 (17)	36 (17)
5 (127)	1 1/2 (38.1)	2 1/8 (54)	1/2 (12.7)	.190 (4.8)	4-12-24 x 1/2	4-12-24 x 1/2	3 ea.	24 ea.	36 (17)	36 (17)
6 (152)	1 1/2 (38.1)	2 1/8 (54)	1/2 (12.7)	.203 (5.2)	4-1/4-20 x 1/2	5-1/4-20 x 1/2	3 ea.	24 ea.	48 (22)	48 (22)